EP EQUIPMENT PRO

CQD14 PRO

LI-ION 80V REACH TRUCK 1.4T

1400 kg | 8000 mm | 80 V Li-Ion

The CQD14/16 PRO series is ideal for high-density warehouses, logistics hubs, and distribution centers. Its optimized mast provides stability at full lift height, while proportional lifting ensures gentle and accurate handling of heavy or fragile goods. With a compact chassis and tight turning radius, it is well-suited for narrow aisles and space-restricted environments. Optional features such as cold storage configuration, safety lamps, and telematics make it adaptable to diverse industry needs.

SPECIFICATION	REF	UNIT	VALUE
Battery type			Li-Ion
Battery nominal capacity K5		Ah	205
Battery voltage		V	80
Rated capacity	Q	kg	1400
Load centre distance	c	mm	600
Service weight		kg	3905
Height, mast lowered	h_1	mm	3383
Lift	h_3	mm	8000
Height, mast extended	h_4	mm	8730
Overall length	l_1	mm	2415
Overall width	b_1/b_2	mm	1250/1270
Length to face of forks	l_2	mm	1265
Fork dimensions	s/e/l	mm	40/100/1150
Turning radius	Wa	mm	1629
Manufacturer			CQD14 PRO
Model designation			EP

Copyright 2026 EP Equipment. All rights reserved. | Datasheet last updated 2026-05-13

Features

Compact and agile design

With a working aisle width of just 2701 mm, the CQD14/16 PRO is perfectly suited for narrow aisles and high-density racking. Its small turning radius adds agility, making it highly competitive in space-constrained warehouses.



Enhanced mast stability

The optimized mast reaches up to 8 m (CQD14 PRO) and 9.65 m (CQD16 PRO), ensuring stability even under heavy loads. High residual capacity at full height guarantees consistent performance in demanding operations.

Efficient Li-ion power system

Powered by an 80V Li-ion battery (150–280Ah), the series supports fast lifting and lowering speeds and offers convenient external charging. The Li-ion system enables opportunity charging and eliminates battery maintenance.

External charging port with a protective cover

Fingertip or joystick hydraulic controls

Operator-focused ergonomics

A spacious cab with unobstructed visibility, electronic steering with damping, and fingertip or joystick controls enhance safety and comfort. Features like proportional lifting and full-color display provide precise handling and ease of use.

Copyright 2026 EP Equipment. All rights reserved. | Datasheet last updated 2026-05-13

VDI Chart

	SPECIFICATION	REF	UNIT	VALUE
1.1	Manufacturer			CQD14 PRO
1.2	Model designation			EP
1.3	Drive			Electric
1.4	Operator type			Seated
1.5	Rated capacity	Q	kg	1400
1.6	Load centre distance	c	mm	600
1.8	Load distance, centre of drive axle to fork	x	mm	340
1.9	Wheelbase	y	mm	1365
2.1	Service weight		kg	3905
2.2	Axle loading, laden front/rear		kg	1085/4250
2.3	Axle loading, unladen front/rear		kg	2495/1415
3.1	Tyres			Polyurethane
3.2	Tyre size, front		mm	Φ343×140
3.3	Tyre size, rear		mm	Φ285×100
3.4	Additional wheels (castor wheels)		mm	-
3.5	Wheels, number front/rear (x=drive wheels)			1x/2
3.6	Tread width, front	b_{10}	mm	–
3.7	Tread width, rear	b_{11}	mm	1168
4.1	Tilt of mast/fork carriage forward/backward		°	2/4
4.2	Height, mast lowered	h_1	mm	3383
4.3	Free lift	h_2	mm	2330
4.4	Lift	h_3	mm	8000
4.5	Height, mast extended	h_4	mm	8730
4.7	Height of overhead guard (cabin)	h6	mm	2200
4.8	Seat height relating to SIP/stand height	h7	mm	1000
4.10	Height of wheel arms		mm	308
4.19	Overall length	l_1	mm	2415
4.20	Length to face of forks	l_2	mm	1265
4.21	Overall width	b_1/b_2	mm	1250/1270
4.22	Fork dimensions	s/e/l	mm	40/100/1150
4.23	Fork carriage ISO 2328, class/type A, B			2A
4.24	Fork carriage width		mm	990

Copyright 2026 EP Equipment. All rights reserved. | Datasheet last updated 2026-05-13

	SPECIFICATION	REF	UNIT	VALUE
4.25	Distance between fork-arms	b_5	mm	200/770
4.26	Distance between wheel arms/loading surfaces			917
4.31	Ground clearance, laden, below mast		mm	75
4.32	Ground clearance, centre of wheelbase	m_2	mm	70
4.34.1	Aisle width for pallets 1000×1200 crossways	Ast	mm	2701
4.34.2	Aisle width for pallets 800 × 1200 lengthways	Ast	mm	2755
4.35	Turning radius	Wa	mm	1629
5.1	Travel speed, laden/unladen		km/h	11/11
5.2	Lift speed, laden/unladen		m/s	0.45/0.6
5.3	Lowering speed, laden/unladen		m/s	0.54/0.5
5.8	Max. gradeability, laden/unladen		%	10/15
5.10	Service brake			Electromagnetic
5.11	Parking brake			Electromagnetic
6.1	Drive motor rating S2 60 min		kW	8
6.2	Lift motor rating at S3 15%		kW	22
6.4	Battery nominal capacity K5		Ah	205
6.4	Battery voltage		V	80
6.4.1	Battery type			Li-Ion
6.5	Battery weight		kg	180
8.1	Type of drive unit			AC
10.5	Steering design			Electronic
10.7	Sound pressure level at the driver's seat		dB(A)	70
15.1	Charger output current		A	100

Copyright 2026 EP Equipment. All rights reserved. | Datasheet last updated 2026-05-13

VDI Drawing



Copyright 2026 EP Equipment. All rights reserved. | Datasheet last updated 2026-05-13



Mast Options

MAST TYPE	LIFT HEIGHT (H3, MM)	MAST LOWERED HEIGHT (H1, MM)	MAST EXTENDED HEIGHT, NO BACKREST (H4, MM)	MAST EXTENDED HEIGHT, WITH BACKREST (H4, MM)	FREE LIFT HEIGHT, NO BACKREST (H2, MM)	FREE LIFT HEIGHT, WITH BACKREST (H2, MM)
3-Free Mast	4000	1968	4730	5065	1044	915
3-Free Mast	4500	2138	5230	5565	1214	1085
3-Free Mast	5000	2303	5730	6065	1380	1250
3-Free Mast	5500	2468	6230	6565	1544	1415
3-Free Mast	6000	2638	6730	7065	1714	1585
3-Free Mast	6500	2810	7230	7565	1888	1757

Copyright 2026 EP Equipment. All rights reserved. | Datasheet last updated 2026-05-13

MAST TYPE	LIFT HEIGHT (H3, MM)	MAST LOWERED HEIGHT (H1, MM)	MAST EXTENDED HEIGHT, NO BACKREST (H4, MM)	MAST EXTENDED HEIGHT, WITH BACKREST (H4, MM)	FREE LIFT HEIGHT, NO BACKREST (H2, MM)	FREE LIFT HEIGHT, WITH BACKREST (H2, MM)
3-Free Mast	7000	3048	7730	8065	2124	1995
3-Free Mast	7500	3218	8230	8565	2294	2165
3-Free Mast	8000	3383	8730	9065	2460	2330

Options

ITEM	OPTIONS (optional items marked in yellow)
Fork dimension	100*40*1150 | 100*40*920 | 100*40*1070 | 100*40*1220 | 100*40*1370 | 100*40*1520
Leg width	917
Fork carriage width option	770mm
Load wheel type	Single
Load wheel material	PU
Drive wheel material	PU
Battery capacity	205Ah | 150Ah | 280Ah
Charger	80V-150A-Li external | 80V-100A-Li external
Seat type	Suspension | Suspension +safety belt logic switch
Attachments	Built-in sideshifter
Anti-static chain	Yes
Castor wheels	No | Yes and not customized
Front lamp	LED
Rear lamp	No | LED
Warning lamp	No | Yes and not customized
Area warning lamp	No | Yes and not customized
Rearview mirror	One in front
Buzzer	No | Yes and not customized
Camera	No | Wireless camera
OPS system	Yes and not customized
Telematics	Yes
Cold storage	No | Yes and not customized
Overhead guard	Yes | Drive-in

Copyright 2026 EP Equipment. All rights reserved. | Datasheet last updated 2026-05-13

ITEM	OPTIONS (optional items marked in yellow)
Turn speed control	Yes
Operator identification device	No | Card reader | Fingerprint lock
Load backrest height	1020mm
Drive assembly	ZK25 | GK25

Copyright 2026 EP Equipment. All rights reserved. | Datasheet last updated 2026-05-13